

Specification for Green Rescue Laser Flare (GLF)													
<b>Model</b>	GLF – Green Rescue Laser Flare												
<b>Wavelength</b>	532nm												
<b>Classification</b>	CW, <5mW, Class IIIa final output power												
<b>Power Supply</b>	One 3V CR123 Lithium Battery Approximate 5 operating hours per battery												
<b>Beam Shape</b>	3 deg. divergent laser line												
<b>NOHD</b> Nominal Ocular Hazard Distance	1mW output at 9', beam width 0.78"												
<b>Operating Temp.</b>	Typical 15° C ~ 45° C												
<b>Laser Operation</b>	Twist cap laser activation												
<b>Construction</b>	Anodized 6061-T6 aluminum, waterproof to 80 feet (24m)												
<b>Dimensions</b>	4.72"(L) x 0.88"(dia.)												
<b>Weight</b>	2.75 oz. without battery												
<b>Dimension Drawing</b>													
<b>Product Label</b>	<div style="border: 1px solid black; padding: 5px;"> <p style="text-align: center;">It is illegal to point this device at an aircraft except in an emergency!</p> <div style="display: flex; justify-content: space-between;"> <div style="width: 45%;"> <p style="text-align: center;"><b>LASER RADIATION</b> AVOID DIRECT EYE EXPOSURE CLASS 3R LASER PRODUCTS 530-680nm, 5mW cw max.</p> <p style="text-align: center;">Complies with: IEC/EN 60825-1, 2007-03 US DHHS 21 CFR Subchapter J</p> </div> <div style="width: 45%; text-align: right;"> <p style="text-align: center;">↑↑ <b>LASER APERTURE</b> ↑↑</p> <p style="font-size: 24pt; font-weight: bold;">Greatland Laser</p> <p>Rancho Cucamonga, CA, USA</p> <p>Model: Green Rescue Laser Flare®</p> <p>Manufactured: 2013 2014 2015</p> <table style="width: 100%; text-align: center;"> <tr> <td>1</td><td>2</td><td>3</td><td>4</td><td>5</td><td>6</td> </tr> <tr> <td>7</td><td>8</td><td>9</td><td>10</td><td>11</td><td>12</td> </tr> </table> <p style="font-size: 24pt; font-weight: bold;">H00001</p> </div> </div> <p style="text-align: center; font-weight: bold;">Serial Number: GLF032-01</p> </div>	1	2	3	4	5	6	7	8	9	10	11	12
1	2	3	4	5	6								
7	8	9	10	11	12								